

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2004 (06.05.2004)

PCT

(10) International Publication Number
WO 2004/038122 A1

(51) International Patent Classification⁷:
F16S 3/00, B21D 47/01, 51/06

E04C 3/07,

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:
PCT/AU2003/001402

(22) International Filing Date: 22 October 2003 (22.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002952221 23 October 2002 (23.10.2002) AU

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant and
(72) Inventor: CHARLWOOD, Grant [AU/AU]; Lot 25
Chain o'Ponds, Mulgoa, NSW 2475 (AU).

Published:
— with international search report

(74) Agent: SPRUSON & FERGUSON; G.P.O. Box 3898,
Sydney, NSW 2001 (AU).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A BEAM



(57) Abstract: A roll formed beam (10) of substantially rectangular cross-section formed from a unity piece of metal. The beam includes opposed first (44) and second (46) substantially parallel walls formed with at least three adjacent layers of said piece of metal (44 a, b, c, and 46 a, b, c). The beam (40) also includes opposed third (48) and fourth (50) substantially parallel walls between the first (44) and second (46) walls. One of the third (48) or fourth (50) walls has a seam (52) joining two opposed longitudinal edges of the piece of metal. A method of roll forming a beam (4) is also disclosed.

WO 2004/038122 A1

EXPRESS MAIL LABEL
NO.: EV 480459425 US